



CABLE TIES CV - black

material: polyamide 6.6

installation temp.: from -10°C to +60°C

working temp.: from -40°C to +85°C

resistance dielectric: 50kV/mm²

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%



TYPE	DIMENSIONS [mm]	max/min BUNDLE DIAMETER [mm]	TENSILE STRENGTH [kg]	PACKAGE [pcs]	COLOR
CV-100MWS	100x1,9	20/3	8	100	■
CV-100MW	100x2,5	20/3	8	100	■
CV-120MW	120x2,5	27/3	8	100	■
CV-140MW	140x2,5	33/3	8	100	■
CV-165MW	160x2,5	43/3	8	100	■
CV-200MW	200x2,5	52/3	8	100	■
CV-140IW	140x3,6	33/3	18	100	■
CV-150IW	150x3,6	36/3	18	100	■
CV-200IW	200x3,6	52/3	18	100	■
CV-250IW	250x3,6	68/3	18	100	■
CV-300IW	280x3,6	78/3	18	100	■
CV-370IW	368x3,6	105/3	18	100	■
CV-160STW	160x4,5	36/3	22	100	■
CV-190STW	190x4,8	49/3	22	100	■
CV-250STW	250x4,5	68/3	22	100	■
CV-300STW	300x4,8	81/3	22	100	■
CV-370STW	368x4,8	100/3	22	100	■
CV-430STW	430x4,8	122/3	22	100	■
CV-500STW	500x4,8	154/3	22	100	■
CV-200HW	200x7,6	50/8	55	100	■
CV-300HW	300x7,6	80/8	55	100	■
CV-370HW	370x7,6	101/8	55	100	■
CV-430HW	450x7,6	128/8	55	100	■
CV-530HW	540x7,6	159/8	55	100	■
CV-770HWL	780x8,8	227/8	80	100	■
CV-830HWL	812x9,0	243/8	80	100	■
CV-1170HWL	1220x9,0	372/8	80	100	■