



CABLE TIES resesable OTW - natural

material: polyamide 6.6

color: natural

installation temp.: -10°C to +60°C






working temp.: -40°C to +85°C

dielectric resistance: 50kV/mm²

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%

TYPE	 DIMENSIONS [mm]	 max/min BUNDLE DIAMETER [mm]	 TENSILE STRENGTH [kg]	 PACKAGE [pcs]	
OTW-100IC	102x3,6	25	18	100	<input type="checkbox"/>
OTW-150STC	150x4,6	39	22	100	<input type="checkbox"/>
OTW-190STC	200x4,6	55	22	100	<input type="checkbox"/>
OTW-300STC	300x4,8	88	22	100	<input type="checkbox"/>
OTW-370STC	370x4,8	102	22	100	<input type="checkbox"/>





CABLE TIES resesable OTW - black

material: polyamide 6.6

color: natural

installation temp.: -10°C to +60°C

working temp.: -40°C to +85°C






dielectric resistance: 50kV/mm²

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%



TYPE	 DIMENSIONS [mm]	 max/min BUNDLE DIAMETER [mm]	 TENSILE STRENGTH [kg]	 PACKAGE [pcs]	
OTW-150HW	150x7,6	35	22	100	■
OTW-200HW	200x7,6	50	22	100	■
OTW-300HW*	300x7,6	80	22	100	■
OTW-500HW*	500x8,5	145	34	100	■

* on request

