



TRYTYTKI CABLE TIES SCK - coloured

material: polyamide 6.6

installation temp.: -10°C to +60°C

working temp.: -40°C to +85°C

dielectric resistance: 50kV/mm²


















humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%

color: red RAL 3017; blue RAL 5002; yellow RAL 1021; green RAL 6024



TYPE	 DIMENSIONS [mm]	 max/min BUNDLE DIAMETER [mm]	 TENSILE STRENGTH [kg]	 PACKAGE [pcs]	
SCK-100MCCR	100x2,5	24/2	11	100	
SCK-100MCNB	100x2,5	24/2	11	100	
SCK-100MCZI	100x2,5	24/2	11	100	
SCK-100MCZO	100x2,5	24/2	11	100	
SCK-140ICCR	140x3,5	36/3	20	100	
SCK-140ICNB	140x3,5	36/3	20	100	
SCK-140ICZI	140x3,5	36/3	20	100	
SCK-140ICZO	140x3,5	36/3	20	100	
SCK-190STCR	200x4,5	51/3	28	100	
SCK-190STNB	200x4,5	51/3	28	100	
SCK-190STZI	200x4,5	51/3	28	100	
SCK-190STZO	200x4,5	51/3	28	100	
SCK-280STCR	280x4,5	101/5	28	100	
SCK-280STNB	280x4,5	101/5	28	100	
SCK-280STZI	280x4,5	101/5	28	100	
SCK-280STZO	280x4,5	101/5	28	100	