



## TRYTYTKI CABLE TIES SCV - black

material: poliamid 6.6

installation temp.: -10°C to +60°C

working temp.: -40°C to +85°C

dielectric resistance: 50kV/mm<sup>2</sup>

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%

TYPE	DIMENSIONS [mm]	max/min BUNDLE DIAMETER [mm]	TENSILE STRENGTH [kg]	PACKAGE [pcs]	COLOR
SCV-100MW	100x2,5	24/2	11	100	■
SCV-140MW	135x2,5	35/2	11	100	■
SCV-165MW	160x2,5	42/2	11	100	■
SCV-200MW	200x2,5	55/2	11	100	■
SCV-140IW	140x3,5	36/3	20	100	■
SCV-200IW	200x3,5	55/3	20	100	■
SCV-250IW	250x3,5	70/3	20	100	■
SCV-300IW	280x3,5	80/3	20	100	■
SCV-370IW	360x3,5	103/3	20	100	■
SCV-190STW	200x4,5	51/3	28	100	■
SCV-250STW	250x4,5	68/5	28	100	■
SCV-280STW	280x4,5	76/5	28	100	■
SCV-370STW	360x4,5	101/5	28	100	■
SCV-430STW	430x4,5	123/5	28	100	■
SCV-200HW	200x7,5	48/5	65	100	■
SCV-300HW	280x7,5	76/5	65	100	■
SCV-370HW	360x7,5	101/5	65	100	■
SCV-430HW	450x7,5	130/20	65	100	■
SCV-530HW	540x7,5	160/20	65	100	■
SCV-750HW	750x7,5	222/32	65	100	■
SCV-770HWL	780x9,0	235/22	80	100	■
SCV-1170HWL	1220x9,0	375/40	80	100	■
SCV-500EHW	500x12,5	140/10	120	50	■
SCV-750EHW	750x12,5	222/40	120	50	■



złącz  
TRYTYT.COM!®