



TRYTYTKI CABLE TIES SGT - natural

material: poliamid 6.6

installation temp.: -10°C to +60°C

working temp.: -40°C to +85°C

dielectric resistance: 50kV/mm²

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%

TYPE	DIMENSIONS [mm]	BUNDLE DIAMETER [mm]	TENSILE STRENGTH [kg]	PACKAGE [pcs]	<input type="checkbox"/>
SGT-100MC	100x2,5	24/2	11	100	<input type="checkbox"/>
SGT-140MC	135x2,5	35/2	11	100	<input type="checkbox"/>
SGT-160MC	160x2,5	42/2	11	100	<input type="checkbox"/>
SGT-200MC	200x2,5	55/2	11	100	<input type="checkbox"/>
SGT-140IC	140x3,5	36/3	20	100	<input type="checkbox"/>
SGT-200IC	200x3,5	55/3	20	100	<input type="checkbox"/>
SGT-250IC	250x3,5	70/3	20	100	<input type="checkbox"/>
SGT-300IC	280x3,5	80/3	20	100	<input type="checkbox"/>
SGT-370IC	360x3,5	103/3	20	100	<input type="checkbox"/>
SGT-190STC	200x4,5	51/3	28	100	<input type="checkbox"/>
SGT-250STC	250x4,5	68/5	28	100	<input type="checkbox"/>
SGT-280STC	280x4,5	76/5	28	100	<input type="checkbox"/>
SGT-370STC	360x4,5	101/5	28	100	<input type="checkbox"/>
SGT-430STC	430x4,5	123/5	28	100	<input type="checkbox"/>
SGT-200HD	200x7,5	48/5	65	100	<input type="checkbox"/>
SGT-300HD	280x7,5	76/5	65	100	<input type="checkbox"/>
SGT-370HD	360x7,5	101/5	65	100	<input type="checkbox"/>
SGT-430HD	450x7,5	130/20	65	100	<input type="checkbox"/>
SGT-530HD	540x7,5	160/20	65	100	<input type="checkbox"/>
SGT-750HD	750x7,5	222/32	65	100	<input type="checkbox"/>
SGT-770HDL	780x9,0	235/22	80	100	<input type="checkbox"/>
SGT-1170HDL	1220x9,0	375/40	80	100	<input type="checkbox"/>
SGT-500EHD	500x12,5	140/10	120	50	<input type="checkbox"/>
SGT-750EHD	750x12,5	222/40	120	50	<input type="checkbox"/>



złącz
TRYTYT.COM!®